

ABOUT US

PyroPro® offer a range of fire protection solutions suitable for suppression of class A, B, C & E fires (RU, pending NZ verification).

Versatile and safe, PyroPro® Tungus® products can be used across a variety of applications; including warehousing, substation, electrical cable channels, document storage facilities, petrochemical/industrial sites, transport, marine and mining.

Developed and thoroughly tested by a leading Russian defence industry enterprise, PyroPro® Tungus® powder firefighting modules are cost effective, with high performance and reliable design features.

Obstruction tolerant, our modules are capable of extinguishing the seat of a fire in any space/ orientation up to 16m height in both closed spaces and outdoors.

PyroPro® Tungus® units are fully independent of power supply or operators on the premises. Manufactured to ISO 9001.



We offer complimentary project specific design. Please contact us with your requirements.



Innovative fire suppression



MPP TUNGUS 9



MPP TUNGUS 10st



MPP TUNGUS 10



MPP TUNGUS 5R



MPP TUNGUS 0.65



MPP TUNGUS 24



Early suppression of fire <
Safe - non pressurized modules <
Non-corrosive <
Autonomous units <
Automatic or manual activation <
Stationary and/or portable <
All direction, high-altitude, no shadow zones <
10 years' operation life, minimal maintenance <



PyroPro® Ltd.
PO Box 251458, Pakuranga,
Auckland 2140, New Zealand
Email: info@pyropro.co.nz
Website: www.pyropro.co.nz

PyroPro® MPP TUNGUS® Performance data

Module name	Extinguishing powder weight (kg)	Application reach Height/Distance (m)	Class A		Class B		Provisional AS/NZS 1850 rating	
			Protected area (m ²)	Protected volume (m ³)	Protected area (m ²)	Protected volume (m ³)	Class A	Class B
MPP TUNGUS 0.65	0.5	small enclosures	1.2	2.4	1.2	1.2	1A	less than 2B
MPP TUNGUS 2	1.9	1-4	25	38	10	13	1A	between 5B-10B
MPP TUNGUS 2.7	2.6	1-4	32.5	65	14	18	1A	10B
MPP TUNGUS 4	4.0	2-9	40	100	18	27	2A	30B
MPP TUNGUS 5/5R	4.4	0-6	78	100	31	40	2A	30B
MPP TUNGUS 6	6.0	2-9	50	150	27	40	2A	30B
MPP TUNGUS 9	8.6	2-13	72	216	33	54	between 2A-3A	30B
MPP TUNGUS 10	9.5	vertically up to 15	36	216	18.3	75	3A	30B
MPP TUNGUS 10st	9.5	2.5-16	80	240	36	60	3A	30B
MPP TUNGUS 24	22.0	max distance 32m	75	250	58	-	4A	greater than 30B



Cable channel



Carpark



Chemical storage



Document storage



Engine room



Factory



Goods storage



Heavy machinery



Mine degassing



Petrochemical




MPP TUNGUS 10st



Substation



Warehouse



Warehouse



MPP TUNGUS 2



MPP TUNGUS 2.7



MPP TUNGUS 4



MPP TUNGUS 5



MPP TUNGUS 6